



PCB connector

Rated current: 15 A

Rated voltage: 300 V

Wire range: 28-12 AWG

Pitch: 5.0 mm/5.08 mm



For reference only!version1.0

UL/CUL

Use Group	B	C	D
Rate Voltage [V]	300	-	300
Rated Current [A]	15	-	10
Wire Range [AWG]	28-12		
Dielectric Voltage-Withstand	1.6KV		

IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	250	320	630
Rated Current [A]	18	18	18
Impulse withstand voltage [KV]	4	4	4
Conductor cross section[solid/flexible] [mm²]	0.2-2.5		

Material

Insulation Material	PA66
---------------------	------

[WJ2EDGRM-THT-5.0/5.08](#)

[WJ2EDGRRM-5.0/5.08](#)

[WJ2EDGVTM-5.0/5.08](#)

[WJ2EDGRTM-5.0/5.08](#)

[WJ2EDGVHM-5.0/5.08](#)

[WJ2EDGRHM-5.0/5.08](#)

[WJ2EDGLM-5.0/5.08](#)

[WJ2EDGKDRN-5.0/5.08](#)

[WJ2EDGKRN-5.0/5.08](#)

[WJ2CDGM-5.0/5.08](#)

[WJ2EDGKRZ-5.0/5.08](#)