


GUK10N-102

GUK Universal combination terminal block

Download date : 2025-12-06



Electrical Diagram :



For reference only!version1.0

CUL Technical Data (UL1059)

Use Group	B	C	D
Rated Voltage [V]	600	600	600
Rated Current [A]	65	65	5
Withstanding Voltage	2200V/1Min		
Wire Range	20-6AWG		

IEC Technical Data (IEC 60947-7-1)

Overvoltage Category	III
Contamination Class	3
Rated Voltage [V]	800V
Rated Current [A]	57A
Impulse withstand voltage	8KV

Conductor cross section

Soild	0.5-16mm ²
Flexible	0.5-10mm ²
Flexible with ferrule	0.5-6mm ²


Material

Insulation Material	PA66
Flame relardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Ni plated

Other Data

Length/Height/Thickness [mm]	42.5/45.8/10.2
Connection Points	2
Stripping Length [mm]	10-11
Type of rail	DIN 35/32
Screw/Torque(Max)[N.m]	M4/1.5-1.8
Operating temperature [°C]	-40~+105

Dimensions




Accessories



[FUKB10-XX](#)



[MUV10-10](#)



[D-GUK3/10-102](#)



[EB-35](#)



[EW-35](#)



[DGL2-35x7.5A](#)



[DGL2-35x7.5B](#)



[DGL2-35x7.5C](#)



[DGL2-35x7.5D](#)



[DGS1-35x7.5W4.2x12](#)



[DGS1-35x7.5W5.2x15](#)



[DGS1-35x7.5W](#)