




PCB spring terminal block

Rated current: 4 A

Rated voltage: 150 V

Wire range: 26-18 AWG

Pitch: 2.54 mm

Mounting: Wave soldering



For reference only!version1.0

UL/CUL

Use Group	B	C	D
Rate Voltage [V]	150	-	-
Rated Current [A]	4	-	-
Wire Range [AWG]	26~18		
Dielectric Voltage-Withstand	1.3KV		

IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	63	160	320
Rated Current [A]	6	6	6
Impulse withstand voltage [KV]	2.5	2.5	2.5
Conductor cross section[solid/flexible] [mm²]	0.2~0.5		

Material

WJ141V-2.54

PCB SPRING TERMINAL BLOCK

Download date : 2025-12-06



Insulation Material	PA66
Flame retardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn Plated

Other Data

Pitch/Poles [mm]/[P]	2.54/1~30
Stripping Length [mm]	11
Screw/Torque(Max)[N.m]	/
Operating temperature [°C]	-40~+105
Soldering temperature	260°C/5S
Pin dimensions [mm]	0.7*0.5
PCB Hole Diameter [mm]	□1.2

Dimensions

PCB opening diagram

