




PCB connector

Rated current: 10 A

Rated voltage: 150 V

Pitch: 3.5 mm

Mounting: Reflow soldering



For reference only!version1.0

## UL/CUL

| Use Group                    | B     | C | D |
|------------------------------|-------|---|---|
| Rate Voltage [V]             | 150   | - | - |
| Rated Current [A]            | 10    | - | - |
| Wire Range [AWG]             | /     |   |   |
| Dielectric Voltage-Withstand | 1.3KV |   |   |

## IEC

|                                               |     |     |     |
|-----------------------------------------------|-----|-----|-----|
| Overvoltage Category                          | III | III | II  |
| Contamination Class                           | 3   | 2   | 2   |
| Rated Voltage [V]                             | 80  | 125 | 200 |
| Rated Current [A]                             | 10  | 10  | 10  |
| Impulse withstand voltage [KV]                | 1.5 | 2.5 | 2.5 |
| Conductor cross section[solid/flexible] [mm²] | /   |     |     |

## Material

|                     |     |
|---------------------|-----|
| Insulation Material | LCP |
|---------------------|-----|

WJ15EDGVHSM-THR-3.5  
PLUG-IN TERMINAL BLOCK

Download date : 2025-12-06




|                              |              |
|------------------------------|--------------|
| Flame retardant rating       | UL94V-0      |
| Conductor Material           | Copper alloy |
| Plating of conductor surface | Sn plated    |

Other Data

|                            |              |
|----------------------------|--------------|
| Pitch/Poles [mm]/[P]       | 3.5/2*2-2*24 |
| Stripping Length [mm]      | /            |
| Screw/Torque(Max)[N.m]     | /            |
| Operating temperature [°C] | -40~+130     |
| Soldering temperature      | 285°C/10S    |
| Pin dimensions [mm]        | 0.8*0.8      |
| PCB Hole Diameter [mm]     | Ø1.4         |

Dimensions


PCB opening diagram




Accessories



[WJ15EDGKSHM-3.5](#)



[WJ15EDGKNHBM-3.5](#)



[WJ15EDGKNHBG-3.5](#)