


|                                                                                   |                                                                                                               |
|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
|  | <p>弹簧式PCB连接器</p> <p>额定电流: 10 A</p> <p>额定电压: 300 V</p> <p>使用线径: 26-14 AWG</p> <p>间距: 5.0 mm</p> <p>安装: 波峰焊</p> |
|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

| 等级 Use Group                     | B     | C | D |
|----------------------------------|-------|---|---|
| 额定电压 Rate Voltage [V]            | 300   | - | - |
| 额定电流 Rated Current [A]           | 10    | - | - |
| 接线范围 Wire Range [AWG]            | 26~14 |   |   |
| 耐电压 Dielectric Voltage-Withstand | 1.6KV |   |   |

技术参数-IEC

|                                          |         |      |      |
|------------------------------------------|---------|------|------|
| 过电压类别 Overvoltage Category               | III     | III  | II   |
| 污染等级 Contamination Class                 | 3       | 2    | 2    |
| 额定电压 Rated Voltage [V]                   | 320     | 320  | 630  |
| 额定电流 Rated Current [A]                   | 17.5    | 17.5 | 17.5 |
| 额定冲击电压 Impulse withstand voltage [KV]    | 4       | 4    | 4    |
| 导线截面积[硬/柔] Conductor cross section [mm²] | 0.2~1.5 |      |      |

材料 Material


|  |  |
|--|--|
|  |  |
|--|--|

|                                     |              |
|-------------------------------------|--------------|
| 绝缘材料 Insulation Material            | PA66         |
| 阻燃等级 Flame relardant rating         | UL94V-0      |
| 导体材料 Conductor Material             | Copper alloy |
| 导体表面镀层 Plating of conductor surface | Sn plated    |

一般参数 Other Data

|                                 |          |
|---------------------------------|----------|
| 间距/极数 Pitch/Poles [mm]/[P]      | 5.0/1~30 |
| 剥线长度 Stripping Length [mm]      | 8        |
| 螺丝/扭矩 Screw/Torque(Max)[N.m]    | /        |
| 工作温度 Operating temperature [°C] | -40~+105 |
| 焊锡温度 Soldering temperature      | 260°C/5S |
| 引针尺寸 Pin dimensions [mm]        | 0.9*0.6  |
| PCB板孔径 PCB Hole Diameter [mm]   | □1.3     |

尺寸图



PCB开孔图

