




目录仅供参考，实际规格依产品工程图为准 版本1.0

技术参数-UL ( 1059 )

|                        |      |     |     |
|------------------------|------|-----|-----|
| 等级 Use Group           | B    | C   | D   |
| 额定电压 Rated Voltage [V] | 600  | 600 | 600 |
| 额定电流 Rated Current [A] | 50   | 50  | 5   |
| 接线范围 Wire Range        | 24-8 |     |     |

技术参数-IEC(60947-7-1)

|                                  |       |
|----------------------------------|-------|
| 过电压类别 Overvoltage Category       | III   |
| 污染等级 Contamination Class         | 3     |
| 额定电压 Rated Voltage               | 1000V |
| 额定电流 Rated Current               | 41A   |
| 额定冲击电压 Impulse withstand voltage | 8KV   |

导线截面积 Conductor cross section

|                                |                         |
|--------------------------------|-------------------------|
| 单芯 Soild                       | 0.2-10.0mm <sup>2</sup> |
| 柔性导线 Flexible                  | 0.2-6.0mm <sup>2</sup>  |
| 柔性导线带冷压头 Flexible with ferrule | 0.25-6.0mm <sup>2</sup> |

材料 Material

|                                     |              |
|-------------------------------------|--------------|
| 绝缘材料 Insulation Material            | PA66         |
| 阻燃等级 Flame relardant rating         | UL94V-0      |
| 导体材料 Conductor Material             | Copper alloy |
| 导体表面镀层 Plating of conductor surface | Sn plated    |

一般参数 Other Data

|                                    |               |
|------------------------------------|---------------|
| 长/高/厚 Length/Height/Thickness [mm] | 44.0/42.0/8.2 |
| 剥线长度 Stripping Length [mm]         | 10-11         |
| 螺丝/扭矩 Screw/Torque(Max)[N.m]       | M4/1.2-1.5    |

尺寸图

