


	插拔式连接器 额定电流: 10 A 额定电压: 300 V 使用线径: 28-12 AWG 间距: 5.0 mm/5.08 mm 接线方式: 直插式弹簧连接
---	--



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

等级 Use Group	B	C	D
额定电压 Rate Voltage [V]	300	-	300
额定电流 Rated Current [A]	10	-	10
接线范围 Wire Range [AWG]	28-12		
耐电压 Dielectric Voltage-Withstand	1.6KV		

技术参数-IEC

过电压类别 Overvoltage Category	III	III	II
污染等级 Contamination Class	3	2	2
额定电压 Rated Voltage [V]	320	320	630
额定电流 Rated Current [A]	12	12	12
额定冲击电压 Impulse withstand voltage [KV]	4	4	4
导线截面积[硬/柔] Conductor cross section [mm²]	0.2-2.5		

材料 Material

--	--



WJ2EDGVM-5.0/5.08



WJ2EDGRM-5.0/5.08



WJ2EDGVM-THT-5.08



WJ2EDGRM-THT-5.08

WJ2EDGLM-5.0/5.08

WJ2EDGKDRN-5.0/5.08

WJ2EDGKRN-5.0/5.08

WJ2CDGM-5.0/5.08