

Rated current: 20A  
Rated voltage: 600V  
Use wire diameter: 26-12AWG



The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

UL ( 1059 )

| Use Group         | B       | C   | D   |
|-------------------|---------|-----|-----|
| Rate Voltage [V]  | 600     | 600 | 600 |
| Rated Current [A] | 20      | 20  | 5   |
| Wire Range [AWG]  | 26 ~ 12 |     |     |

IEC ( 60947-7-1 )

|                             |         |
|-----------------------------|---------|
| Rated Voltage [V]           | 800     |
| Rated Current [A]           | 24      |
| Soild [mm²]                 | 0.2-4.0 |
| Flexible [mm²]              | 0.2-2.5 |
| Flexible with ferrule [mm²] | 0.2-2.5 |

|                                |     |
|--------------------------------|-----|
| Overvoltage Category           | III |
| Contamination Class            | 3   |
| Impulse withstand voltage [KV] | 8   |


Material

|                              |              |
|------------------------------|--------------|
| Insulation Material          | PA66         |
| Flame relardant rating       | UL94V-0      |
| Conductor Material           | Copper alloy |
| Plating of conductor surface | Sn plated    |


Other Date

|                              |               |
|------------------------------|---------------|
| Length/Height/Thickness [mm] | 72.4/35.4/5.2 |
| Stripping Length [mm]        | 8-10          |

Dimensions



Accessories




FUVA2.5-XX




DUV2.5-104




MUV2.5-10



PUV2.5-96




EB-35




EW-35



DGL2-35x7.5A



DGL2-35x7.5B



DGL2-35x7.5C



DGL2-35x7.5D