


Rated current: 20A

Rated voltage: 300V

Use wire diameter: 26-12AWG

spacing:5.0mm

Install: Wave soldering

The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

UL/CUL

Use Group	B	C	D
Rate Voltage [V]	300	-	300
Rated Current [A]	20	-	10
Wire Range [AWG]	26～12		
Dielectric Voltage-Withstand	1.6KV		

IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	250	400	630
Rated Current [A]	24	24	24

Impulse withstand voltage [KV]	4	4	4
Conductor cross section [mm²]	0.2~2.5		

Material


Insulation Material	PA66
Flame relardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated


Other Date

Pitch/Poles [mm]/[P]	5.0/2～24
Stripping Length [mm]	5～6
Screw/Torque(Max)[N.m]	M2.6/0.4
Operating temperature [℃]	-40～+105
Soldering method	Wave soldering
Pin dimensions [mm]	Ø1.05
PCB Hole Diameter [mm]	Ø1.3

Dimensions

PCB hole diagram


ø1.05
5.00XX
0.60
5.00
3.50
11.40
5.50
9.00
5.00(XX-1)


5.0(XX-1)
ø1.30
11.40
5.50
5.00
P.C.B. LAYOUT