


Rated current: 30A

Rated voltage: 300V

Use wire diameter: 26-10AWG

spacing:7.62mm

Install: Wave soldering

The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

UL/CUL

Use Group	B	C	D
Rate Voltage [V]	300	-	300
Rated Current [A]	30	-	10
Wire Range [AWG]	26～10		
Dielectric Voltage-Withstand	1.6KV		

IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	500	630	1000
Rated Current [A]	32	32	32

Impulse withstand voltage [KV]	6	6	6
Conductor cross section [mm²]	0.2~4.0		

Material


Insulation Material	PA66
Flame relardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated


Other Date

Pitch/Poles [mm]/[P]	7.62/2-24
Stripping Length [mm]	6-7
Screw/Torque(Max)[N.m]	M3/0.5
Operating temperature [℃]	-40～+105
Soldering method	Wave soldering
Pin dimensions [mm]	0.8*1.0
PCB Hole Diameter [mm]	Ø1.5

Dimensions

PCB hole diagram


12.50
0.55
7.62XX
21.50
0.80
4.75
4.60
(4.40)
7.62
1.00
7.62(XX-1)


(4.40)
7.62(XX-1)
7.62
4.60
12.50
ø1.50
P.C.B. LAYOUT