

Rated current: 16A

Rated voltage: 300V

spacing:5.0mm

Install: Reflow Soldering

The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

## UL/CUL

| Use Group | B | C | D |
|---|---|---|---|
| Rate Voltage [V] | 300 | - | 300 |
| Rated Current [A] | 16 | - | 10 |
| Wire Range [AWG] | | - | |
| Dielectric Voltage-Withstand | | 1.6KV | |

## IEC

| Overvoltage Category | III | III | II |
|---|---|---|---|
| Contamination Class | 3 | 2 | 2 |
| Rated Voltage [V] | 160 | 160 | 320 |
| Rated Current [A] | 20 | 20 | 20 |

| | | | |
|---|---|---|---|
| Impulse withstand voltage [KV] | 4 | 4 | 4 |
| Conductor cross section [mm²] | | - | |


## Material

| | |
|---|---|
| Insulation Material | PA66 |
| Flame relardant rating | UL94V-0 |
| Conductor Material | Copper alloy |
| Plating of conductor surface | Au plated area |


## Other Date

| | |
|---|---|
| Pitch/Poles [mm]/[P] | 5.0/02,04-14 |
| Stripping Length [mm] | - |
| Screw/Torque(Max)[N.m] | - |
| Operating temperature [℃] | -40～+105 |
| Soldering method | Reflow Soldering |

## Dimensions




## PCB hole diagram



## Accessories



WJ9KS-5.0