


Rated current: 20A

Rated voltage: 300V

Use wire diameter: 28-12AWG

spacing:5.0mm

The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

UL/CUL

Use Group	B	C	D
Rate Voltage [V]	300	-	300
Rated Current [A]	20	-	10
Wire Range [AWG]	28-12		
Dielectric Voltage-Withstand	1.6KV		

IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	320	320	630
Rated Current [A]	32	32	32

Impulse withstand voltage [KV]	4	4	4
Conductor cross section [mm²]	0.2-4.0		

Material


Insulation Material	PA66
Flame relardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated


Other Date

Pitch/Poles [mm]/[P]	5.0/1-24
Stripping Length [mm]	9-10
Screw/Torque(Max)[N.m]	-
Operating temperature [℃]	-40～+105
Soldering method	Wave soldering
Pin dimensions [mm]	1.2*0.8
PCB Hole Diameter [mm]	Ø1.8

Dimensions

PCB hole diagram


22.90
5.00XX+1.50
19.00
4.00
ø0.80
10.00
6.15
1.20
5.00
2.90
5.00(XX-1)


5.00(XX-1)
2.90
5.00
22.90
10.00
6.15
P.C.B. LAYOUT
ø1.80