

Rated current: 15A

Rated voltage: 300V

Use wire diameter: 26-14AWG

spacing:5.08mm

Install: Wave soldering

The catalog is for reference only. The actual specifications are subject to the product engineering drawings. version 1.0

UL/CUL

Use Group	B	C	D
Rate Voltage [V]	300	-	300
Rated Current [A]	15	-	10
Wire Range [AWG]	26～14		
Dielectric Voltage-Withstand	1.6KV		

IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	250	400	630
Rated Current [A]	17.5	17.5	17.5

Impulse withstand voltage [KV]	4	4	4
Conductor cross section [mm²]	0.5~1.5		

Material


Insulation Material	PA66
Flame relardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated


Other Date

Pitch/Poles [mm]/[P]	5.08/2-24
Stripping Length [mm]	6-7
Screw/Torque(Max)[N.m]	M3/0.5
Operating temperature [℃]	-40 ~ +105
Soldering method	Wave soldering
Pin dimensions [mm]	0.5*1.0
PCB Hole Diameter [mm]	Ø1.4

Dimensions

PCB hole diagram


12.10
5.08XX+0.92
11.14
0.50
6.05
3.50
1.00
5.08
5.08(XX-1)
3.00


5.08(XX-1)
5.08
3.00
ø1.40
6.05
12.10
P.C.B. LAYOUT