




额定电流: 40A  
额定电压: 600V  
使用线径: 18-10AWG  
间距:13.0mm



目录仅供参考，实际规格依产品工程图为准 版本1.0

材质及电镀 Material

|               |                          |
|---------------|--------------------------|
| 螺丝 Screws     | M4.0 Steel Ni plated     |
| 焊脚 Pin Header | Copper alloy , Sn plated |
| 塑件 Housing    | PA66 , UL94V-0           |


电气性能 Electrical

|                            |              |
|----------------------------|--------------|
| 参考标准 Standard              | UL           |
| 额定电压 Rated voltage         | 600V         |
| 额定电流 Rated current         | 40A          |
| 使用线径 Wire range            | 18-10AWG     |
| 接触电阻 Contact Resistance    | 20mΩ         |
| 绝缘电阻 Insulation resistance | 500MΩ/DC500V |
| 耐电压 Withstanding voltage   | AC2200V/1Min |

一般参数 Other Date

|                                 |            |
|---------------------------------|------------|
| 间距/极数 Pitch/Poles [mm]/[P]      | 13.0/2-20  |
| 工作温度 Operating temperature [°C] | -40 ~ +105 |
| 扭矩 Torque                       | 1.2N.m     |

尺寸图



PCB开孔图

