

额定电流: 65A  
额定电压: 600V  
使用线径: 14-6AWG  
间距:16.0mm



目录仅供参考，实际规格依产品工程图为准 版本1.0

材质及电镀 Material

|               |                          |
|---------------|--------------------------|
| 螺丝 Screws     | M5.0 Steel Zn plated     |
| 焊脚 Pin Header | Copper alloy , Sn plated |
| 塑件 Housing    | PBT , UL94V-0            |


电气性能 Electrical

|                            |               |
|----------------------------|---------------|
| 参考标准 Standard              | UL            |
| 额定电压 Rated voltage         | 600V          |
| 额定电流 Rated current         | 65A           |
| 使用线径 Wire range            | 14-6AWG       |
| 接触电阻 Contact Resistance    | 20mΩ          |
| 绝缘电阻 Insulation resistance | 1000MΩ/DC500V |
| 耐电压 Withstanding voltage   | AC2500V/1Min  |

一般参数 Other Date

|                                 |                             |
|---------------------------------|-----------------------------|
| 间距/极数 Pitch/Poles [mm]/[P]      | 16.0/1-15                   |
| 工作温度 Operating temperature [°C] | -40 ~ +130                  |
| 扭矩 Torque                       | 25.5Kgf.cm/2.5N.m/22.1Lb.in |

尺寸图



PCB开孔图

