

贯通式接线端子

额定电流: 15A

额定电压: 300V

使用线径: -

间距:12.0mm

安装: 波峰焊接

目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

等级 Use Group	B	C	D
额定电压 Rate Voltage [V]	300	300	300
额定电流 Rated Current [A]	15	15	10
接线范围 Wire Range [AWG]	-		
耐电压 Dielectric Voltage-Withstand	1.6KV		

技术参数-IEC

过电压类别 Overvoltage Category	III	III	II
污染等级 Contamination Class	3	2	2
额定电压 Rated Voltage [V]	400	630	1000
额定电流 Rated Current [A]	20	20	20
额定冲击电压 Impulse withstand voltage [KV]	6	6	6

导线截面积[硬/柔] Conductor cross section [mm²]	-
--	---


材料 Material

绝缘材料 Insulation Material	PA66
阻燃等级 Flame relardant rating	UL94V-0
导体材料 Conductor Material	Copper alloy
导体表面镀层 Plating of conductor surface	Sn plated

一般参数 Other Date

间距/极数 Pitch/Poles [mm]/[P]	12.0/1-12
焊接方式 Soldering method	Wave soldering
引针尺寸 Pin dimensions [mm]	0.8*2.8
工作温度 Operating temperature [°C]	-40 ~ +105
PCB板孔径 PCB Hole Diameter [mm]	3.0*1.0

尺寸图



PCB开孔图

