




额定电流: 5A
额定电压: 300V
使用线径: 22-18AWG
间距:3.81mm



目录仅供参考，实际规格依产品工程图为准 版本1.0

技术数据-UL/CUL

等级 Use Group	B	C	D
额定电压 Rate Voltage [V]	300	-	300
额定电流 Rated Current [A]	5	-	5
接线范围 Wire Range [AWG]	22-18		
耐电压 Dielectric Voltage-Withstand	1.6KV		

技术参数-IEC

过电压类别 Overvoltage Category	III	III	II
污染等级 Contamination Class	3	2	2
额定电压 Rated Voltage [V]	200	320	500
额定电流 Rated Current [A]	17.5	17.5	17.5
额定冲击电压 Impulse withstand voltage [KV]	4	4	4

导线截面积[硬/柔] Conductor cross section [mm²]

0.5~1.5/0.75~1.5

材料 Material

绝缘材料 Insulation Material

PA66

阻燃等级 Flame retardant rating

UL94V-0

导体材料 Conductor Material

Copper alloy

导体表面镀层 Plating of conductor surface

Sn plated

一般参数 Other Data

间距/极数 Pitch/Poles [mm]/[P]

3.81/1-30

剥线长度 Stripping Length [mm]

9-10

螺丝/扭矩 Screw/Torque(Max)[N.m]

-

工作温度 Operating temperature [°C]

-40 ~ +105

焊接方式 Soldering method

Wave soldering

引针尺寸 Pin dimensions [mm]

0.8*0.4

PCB板孔径 PCB Hole Diameter [mm]

Ø1.2

尺寸图

PCB开孔图

