


Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除予明确授权外，擅自复制或传播本文件内容，侵犯者将承担法律责任。本公司保留对涉及发明、实用新型和外观设计的所有权利。





General Tolerances								— ▯ ⊥		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

5	Clamp	Copper Alloy	Ni Plated
4	Screw	Steel	M2/Zn Plated
3	Cage	Copper Alloy	M2/Ni Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

DES.	YaoFei	DATE	23.10.12	UNITS	mm	THIRD ANGLE PROJECTION	
CHK.	YangHJ	DATE	23.10.12	SIZE	A4	TYPE: CUSTOMER DRAWING	
APP.	JASON	DATE	23.10.12	SCALE	3:1	DRAWING TYPE: SP-03	
PART NO.: WJ15EDGK-3.5-XXP-1Y-00A						REV	0

REVISION RECORD					
REV.	ESCRPTION		ECN No.	APPROVED	DATE
0	新发行			YaoFei	23.10.12

UL/CUL 技术参数								
UL/CUL Technical Data								
等级	Use Group					B	C	D
额定电压	Rated Voltage [V]					300	-	300
额定电流	Rated Current [A]					8	-	8
接线范围	Wire Range					28-16		
单/多芯线	Solid/Stranded [AWG]							
耐电压	Withstanding Voltage	1600V/1Min						
IEC 技术参数								
IEC Technical Data								
过电压类别	Overvoltage Category					III	III	II
污染等级	Contamination Class					3	2	2
额定电压	Rated Voltage [V]					160	160	250
额定电流	Rated Current [A]					7	7	7
额定冲击电压	Impulse withstand voltage [KV]					2.5	2.5	2.5
导线截面积	Conductor cross section					0.5-1.5		
硬质/柔性导线	Solid/flexible [mm²]							
一般参数						Other Data		
间距	Pitch / 极数 Poles [mm] / [P]					3.5 / 02~24		
剥线长度	Stripping Length [mm]					6~7		
螺丝	Screw/扭矩 Torque(Max) [N.m]					M2/0.2		
工作温度	Operating temperature [°C]					-40~105		
符合RoHS环保要求								