


Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除丰捷予明确授权，否则禁止转让、复制、利用、交流本文件的内容。侵犯者将承担赔偿责任。 本公司保留对涉及发明、实用新型和外观专利的所有权利。



General Tolerances								— ▯ ⊥		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

5	Clamp	Copper Alloy	Ni Plated
4	Screw	Steel	M3/Zn Plated
3	Cage	Copper Alloy	M3/Ni Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

REVISION RECORD									
REV.	DESCRIPTION					ECN No.	APPROVED	DATE	
0	新发行						YaoFei	24.01.17	

UL/CUL 技术参数
UL/CUL Technical Data

等级	Use Group	B	C	D			
额定电压	Rated Voltage [V]	300	-	300			
额定电流	Rated Current [A]	15	-	10			
接线范围	Wire Range	28-12					
单/多芯线	Solid/Stranded [AWG]						
耐电压	Withstanding Voltage	1600V/1Min					
IEC 技术参数 IEC Technical Data							
IEC61984							
过电压类别	Overvoltage Category	III	III	II			
污染等级	Contamination Class	3	2	2			
额定电压	Rated Voltage [V]	250	320	630			
额定电流	Rated Current [A]	12	12	12			
额定冲击电压	Impulse withstand voltage [KV]	4.0	4.0	4.0			
导线截面积	Conductor cross section	0.2-2.5					
硬质/柔性导线	Solid/flexible [mm²]						
一般参数 Other Data							
间距	Pitch /极数 Poles [mm]/[P]	5.0 / 02~24					
剥线长度	Stripping Length [mm]	7~8					
螺丝	Screw/扭矩 Torque(Max) [N.m]	M3/0.5					
工作温度	Operating temperature [°C]	-40~105					
符合RoHS环保要求							

DES.	YaoFei	DATE	24.01.17	UNITS	mm	THIRD ANGLE PROJECTION			
CHK.	YangHJ	DATE	24.01.17	SIZE	A4	TYPE: CUSTOMER DRAWING		SHEET 1 of 1	
APP.	JASON	DATE	24.01.17	SCALE	5:2	DRAWING TYPE: SP-03		REV	0
慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ2EDGKB-5.0-XXP-1Y-00A			

FOR-0371 Rev.1.0