





Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非经予明确授权, 否则禁止转让、复制、利用、交流本文件的内容。侵犯者将承担赔偿责任, 实用新型和外观设计专利的所有权利。



P.C.B. LAYOUT

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
0	新发行		WangP	24.03.27

UL/CUL 技术参数		UL/CUL Technical Data			
等 级	Use Group	B	C	D	
额定电压	Rated Voltage [V]	600	-	600	A
额定电流	Rated Current [A]	15	-	5	
接线范围	Wire Range	-			B
单/多芯线	Solid/Stranded [AWG]				
耐电压	Withstanding Voltage	2200V/1Min			C
IEC 技术参数		IEC61984			
IEC Technical Data					D
过电压类别	Overvoltage Category	III	III	II	
污染等级	Contamination Class	3	2	2	A
额定电压	Rated Voltage [V]	630	1000	1000	
额定电流	Rated Current [A]	15	15	15	B
额定冲击电压	Impulse withstand voltagea [KV]	6.0	6.0	6.0	
导线截面积	Conductor cross section	-			C
硬质/柔性导线	Solid/ flexible [mm²]				
一般参数		Other Data			D
间距 Pitch / 极数 Poles	[mm] / [P]	10.0 / 02~12			
剥线长度	Stripping Length [mm]	-			A
螺丝 Screw/ 扭矩 Torque(Max)	[N.m]	-			
工作温度	Operating temperatur [°C]	-40~105			B

General Tolerances

								—	∠	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

3	Nut	Copper Alloy	M2.5
2	Pin	Copper Alloy	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

DES.	WangP	DATE	24.03.27	UNITS	mm	THIRD ANGLE PROJECTION	
CHK.	YangHJ	DATE	24.03.27	SIZE	A4	TYPE: CUSTOMER DRAWING	
APP.	JASON	DATE	24.03.27	SCALE	3:1	DRAWING TYPE: SP-03	
慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ2EDGVM-10.0-XXP-2Y-00A	
FOR-0371 Rev.1.0						SHEET 1 of 1 REV 0	