



Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除专利、实用新型、外观设计、发明专利、实用新型和外观设计专利的所有权利。



REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		WangZF	24.12.05

UL/CUL 技术 参数		UL/CUL Technical Data			
等 级	Use Group	B	C	D	
额定电压	Rated Voltage [V]	300	-	300	
额定电流	Rated Current [A]	15	-	10	
接线范围	Wire Range	28-12			
单/多芯线	Solid/Stranded [AWG]				
耐电压	Withstanding Voltage	1600V/1Min			
IEC 技术参数					
IEC Technical Data					
过电压类别	Overvoltage Category	III	III	II	
污染等级	Contamination Class	3	2	2	
额定电压	Rated Voltage [V]	320	320	630	
额定电流	Rated Current [A]	16	16	16	
额定冲击电压	Impulse withstand voltagea [KV]	4.0	4.0	4.0	
导线截面积	Conductor cross section	0.25-2.5			
硬质/柔性导线	Solid/ flexible [mm ²]				
材 料		Material			
绝缘材料	Insulation Material	PA66			
阻燃等级	Imflammability	UL94V-0			
导体材料	Contacting Material	铜合金 Copper alloy			
导体表面镀层	Contactive Coating	镀锡 Sn Plated			
一般参数 Other Data					
间距 Pitch / 极数 Poles	[mm] / [P]	5.08/ 02~24			
剥线长度	Stripping Length [mm]	8~9			
工作温度	Operating temperatur [°C]	-40~105			

General Tolerances

variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	— □ ⊥		
								to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

6	Spring	Stainless steel	/
5	Clamp	Copper Alloy	Sn Plated
4	Cover2	PA66	UL94V-0
3	Cover1	PA66	UL94V-0
2	Housing2	PA66	UL94V-0
1	Housing1	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

DES.	WangZF	DATE	24.12.05	UNITS	mm	THIRD ANGLE PROJECTION	
CHK.	HuHT	DATE	24.12.05	SIZE	A4	TYPE: CUSTOMER DRAWING	
APP.	Jason	DATE	24.12.05	SCALE	2:1	DRAWING TYPE: SP-03	
						REV	V0
						PART NO.: WJ0501-05XX-1Y-00N	



慈溪市万捷电子有限公司
CIXI WANJIE ELECTRONIC CO., LTD