





Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权, 否则禁止转让、复制、利用、交流本文件的内容。侵犯者将承担赔偿责任。 本公司保留对专利及发明、实用新型和外观设计的所有权利。




P.C.B. LAYOUT



REVISION RECORD					
REV.	ESCRPTION		ECN No.	APPROVED	DATE
V0	新发行			WangZF	24.12.06

UL/CUL 技术参数				
UL/CUL Technical Data				
等 级	Use Group	B	C	D
额定电压	Rated Voltage [V]	300	-	300
额定电流	Rated Current [A]	15	-	10
接线范围	Wire Range	28-12		
单/多芯线	Solid/Stranded [AWG]			
耐电压	Withstanding Voltage	1600V/1Min		

IEC 技术参数				
IEC Technical Data				
过电压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	320	320	630
额定电流	Rated Current [A]	12	12	12
额定冲击电压	Impulse withstand voltagea [KV]	4	4	4
导线截面积	Conductor cross section	0.25-2.5		
硬质/柔性导线	Solid/ flexible [mm²]			

材 料				
绝缘材料	Insulation Material			
阻燃等级	Imflammability			
导体材料	Contactior Material			
导体表面镀层	Contactive Coating	镀锡 Sn Plated		

一般参数				
间距	Pitch / 极数 Poles [mm] / [P]			
工作温度	Operating temperatur [°C]			
剥线长度	Stripping Length [mm]			
焊锡温度	Soldering temperature			
引针尺寸	Pin Dimensions [mm]			
PCB板孔径	PCB Hole Diameter [mm]			

WangZF	DATE	24.12.06	UNITS	mm	THIRD ANGLE PROJECTION		
HuHT	DATE	24.12.06	SIZE	A4	TYPE: CUSTOMER DRAWING		SHEET 1 of 1
Jason	DATE	24.12.06	SCALE	2:1	DRAWING TYPE: SP-03		REV V0

 慈 溪 市 万 捷 电 子 有 限 公 司 CIXI WANJIE ELECTRONIC CO.,LTD					PART NO.: WJ0704-02XX-1Y-00A	
---	--	--	--	--	---------------------------------	--

General Tolerances								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	to 10	over 10 to 100	over 100 to	
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60