




Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除经明确授权, 否则禁止转让、复制、利用、交本文件的内容。侵犯者将负赔偿责任。本公司保留因涉及发明、实用新型和外观设计的所有权利。



General Tolerances								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

6	Pin header	Copper Alloy	Sn Plated
5	Spring	Stainless steel	/
4	Cover2	PA66	UL94V-0
3	Cover1	PA66	UL94V-0
2	Housing2	PA66	UL94V-0
1	Housing1	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

REVISION RECORD									
REV.	DESCRIPTION				ECN No.	APPROVED	DATE		
V0	新发行					WangZF	24.12.05		
UL/CUL 技术参数 UL/CUL Technical Data									
等级		Use Group			B	C	D		
额定电压		Rated Voltage [V]			300	-	300		
额定电流		Rated Current [A]			15	-	10		
接线范围		Wire Range			28-12				
单/多芯线		Solid/Stranded [AWG]							
耐电压		Withstanding Voltage			1600V/1Min				
IEC 技术参数					IEC61984				
IEC Technical Data									
过电压类别		Overvoltage Category			III	III	II		
污染等级		Contamination Class			3	2	2		
额定电压		Rated Voltage [V]			320	320	630		
额定电流		Rated Current [A]			12	12	12		
额定冲击电压		Impulse withstand voltage [KV]			4	4	4		
导线截面积		Conductor cross section			0.25-2.5				
硬质/柔性导线		Solid/ flexible [mm²]							
材料		Material							
绝缘材料		Insulation Material			PA66				
阻燃等级		Imflammability			UL94V-0				
导体材料		Contactor Material			铜合金 Copper alloy				
导体表面镀层		Contactive Coating			镀锡 Sn Plated				
一般参数		Other Data							
间距		Pitch / 极数 Poles [mm] / [P]			5.08 / 02~24				
工作温度		Operating temperatur [°C]			-40~105				
剥线长度		Stripping Length [mm]			8-9				