

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非经书面授权, 否则禁止转让、复制、利用、交流本文档的内容。未经许可擅自涉及复制、使用等行为, 侵权者将承担相关法律责任。

24.40

9.50

9.50(XX-1)

φ2.00

P.C.B. LAYOUT

18.00

0.80

General Tolerances

— ▯ ⊥

variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

9.50(XX+2)

9.90

9.50(XX-1)

5.00±0.30

16.30

电气性能/Electrical
额定电压 /Rated voltage 300V
额定电流 /Rated current 20A
接触电阻 /Contact resistance 20mΩ
绝缘电阻 /Insulation resistance 500MΩ/DC500V
使用线径 /Wire range 22~12AWG
耐电压 /With standing voltage AC 1600V/1 Min
机械性能/Mechanica
扭 矩/Torque 1.2Nm(10.6Lb.in)
温度范围 /Temp.Range -40°C~+105°C
瞬时温度 /MAX Soldering +260°C, for 5 Sec
尺 寸/Dimensions
间 距/Pitch 9.5mm
极 数/Poles 2~22p

9.50

1.50

9.65

6.80

2

1

3

3	Pin Header	Copper Alloy	Sn Plated
2	Screws	Steel	M4 Steel Ni plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

DES.	ZhaoXY	DATE	24.04.01	UNITS	mm	THIRD ANGLE PROJECTION	⊕
CHK.	HuHT	DATE	24.04.01	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1
APP.	Jason	DATE	24.04.01	SCALE	2:1	DRAWING TYPE: SP-03	REV V1
 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ45RM-XXP-1Y-00A	

FOR-0371 Rev.1.0