



慈溪市万捷电子有限公司

CIXI WANJIE ELECTRONIC CO., LTD


REVISION RECORD

REV.	DESCRIPTION	ECN No.	APPROVED	DATE

UL/CUL 技术参数 (UL1059)
UL/CUL Technical Data



等 级	Use Group	B	C	D	
额定电压	Rated Voltage	[V]	-	-	-
耐电压	Withstanding Voltage	1600V/1Min			
接线范围	Wire Range	26-14			
单/多芯线	Solid/Stranded				
IEC 技术参数 (IEC60947-7-2) IEC Technical Data					
过电压类别	Overvoltage Category	III			
污染等级	Contamination Class	3			
额定电压	Rated Voltage	[V]	-		
额定冲击电压	Impulse withstand voltagea	[KV]	6		
导线截面积 Conductor cross section					
单芯	Solid	[mm²]	0.2-1.5		
柔性导线	flexible	[mm²]	0.2-1.5		
柔性导线带冷压头	flexible with ferrule	[mm²]	0.2-1.0		
材 料 Material					
绝缘材料	Insulation Material	PA66			
阻燃等级	Imflammability	UL94V-0			
导体材料	Contact Material	铜合金 Copper alloy			
导体表面镀层	Contactive Coating	镀锡 Sn Plated			
一般参数 Other Data					
连接点数	connection points	3			
剥线长度	Stripping Length	[mm]	8-10		
导轨类型	Type of rail	DIN 35			
螺丝	Screw/扭矩 Torque(Max)	[N.m]	--		
工作温度	Operating temperatur	[°C]	-40-105		



linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to		over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

黄绿色/green-yellow	GUV1.5-103-PE-00A
颜色/Colour	订货号 /Order No.

单位 / UNITS	mm	尺寸 / SIZE	A4	比例 / SCALE	1:1	第三视角/THIRD ANGLE PROJECTION	版本 / REV	V0
						名称 / TITLE	GUV1.5-103-PE-00A	



慈溪市万捷电子有限公司
CIXI WANJIE ELECTRONIC CO., LTD