



慈溪市万捷电子有限公司
CIXI WANJIE ELECTRONIC CO., LTD

35.40

29.40

UL/CUL 技术参数 (UL1059)										cULus	
UL/CUL Technical Data											
等级	Use Group	B	C	D							
额定电压	Rated Voltage	V	600	600	600						
额定电流	Rated Current	A	30	30	5						
耐电压	Withstanding Voltage	2200V/1Min									
接插范围	Wire Range	24-10									
导体芯线	Solid/Stranded	AWG									
IEC 技术参数 (IEC8004-7-1)											
IEC Technical Data											
过电压类别	Overvoltage Category	III									
污染等级	Contamination Class	3									
额定电压	Rated Voltage	V	800								
额定电流	Rated Current	A	32								
额定开断电压	Rated breaking voltage	kV	8								
导线截面面积	Conductor cross section										
单芯	Solid	mm ²	0.25.0								
柔性导线	flexible	mm ²	0.24.0								
柔性导线带冷压头	flexible with ferrule	mm ²	0.24.0								
材料											
绝缘材料	Insulation Material	PA66									
阻燃等级	Inflammability	UL94V-0									
导体材料	Conductor Material	铜合金 Copper alloy									
导体表面镀层	Conductive Coating	镀锡 Sn Plated									
一般参数											
连接点数	connection points	4									
剥线长度	Stripping Length	mm	8-10								
导线类型	Type of rail	DN 35									
螺丝	Screw/扭矩	Torque(Max)	-								
工作温度	Operating temperatur	°C	-40/-105								

linear dimension (Tolerances Standard GB/T 14486-2008)	—		
--	---	---	---

红色/Red	GUS4-104-RD-00A
黑色/Black	GUS4-104-BK-00A

tolerance	± 0.20	± 0.30	± 0.50	± 0.70	± 1.00	± 1.30	± 1.60	0.10	0.30	0.60
variable range	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100	over 100 to 100	over 100 to 100

单位 / UNITS	mm	尺寸 / SIZE	A4	比例 / SCALE	1:1
慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD					
					
名称 / TITLE			第三角制 / THIRD ANGLE PROJECTION 		
GUS4-104-XX-00A			版本 / REV V0		