




G		Pipe	Shield Pipe,Brass With Nickel Plated	pcs	1
F		O-ring	O-ring,FKM Green	pcs	1
E		TPU	Molded With Black TPU	G	8
D		Housing	A-Coding Female 12PIN,Black PA66	pcs	1
C		Terminal	Female Terminal ,Brass With Gold Plated	pcs	12
B		Screw	Screw M12 X1.0,Brass With Nickel Plated	pcs	1
A		Cable	UL TYPE 26AWG X12C+AL+Braid Black PVC Jacket	mm	L
编号 No.	料号 Materials.No	品名 Name	材料规格 Description	单位 Unit	用量 Qty

IEC 技术参数		IEC61076-2-101
IEC Technical Data		
工作温度	Operating temperature [°C]	-25~+80
防护等级	IP Class (IN Locked condition)	IP67
额定电压	Rated Voltage [V]	30
额定电流	Rated Current [A]	1.5
导线截面积	Conductor cross section	0.14
硬质/柔性导线	Solid/ flexible [mm²]	
接线范围	Wire Range	26
单/多芯线	Solid/Stranded [AWG]	
材料	Material	
绝缘材料	Insulation Material	PA 66
阻燃等级	Imflammability	UL94V-0
导体材料	Contactior Material	铜合金 Copper alloy
导体镀层	Contactive Coating	镀金 Gold Plated
螺母/螺丝	Connector Nut/Screw	Brass With Nickel Plated 铜镀镍
符合RoHS环保要求		

 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD							PART NO.: M12-A12-ST2-F02-BCC- <u>XXX</u>			
NO SPECIFIED TOLERANCE			Cus' P/N:		Order No. : ---		Drawing No.:		SP-02-M0XXXX	
LINEAR	0.5-6	±0.1	DES.	JUN	DATE	UNITS	mm	THIRD ANGLE PROJECTION		PAGE
	6~30	±0.2							1 of 1	
	>30	±2%								
ANGLES	±1°		APP.		DATE	SCALE	X:X	文件等级:外部公开		