



IEC 技术参数		IEC61076-2-101
IEC Technical Data		
工作温度	Operating temperature [°C]	-40~+80
防护等级	IP Class (IN Locked condition)	IP67
额定电压	Rated Voltage [V]	30
额定电流	Rated Current [A]	1.5
导线截面积	Conductor cross section	0.14
硬质/柔性导线	Solid/ flexible [mm²]	
接线范围	Wire Range	26
单/多芯线	Solid/Stranded [AWG]	
材料 Material		
绝缘材料	Insulation Material	PA 66
阻燃等级	Imflammability	UL94V-0
导体材料	Contactore Material	铜合金 Copper alloy
导体镀层	Contactive Coating	镀金 Gold Plated
螺母/螺丝	Connector Nut/Screw	Copper Alloy With Nickel Plated铜镀镍
符合RoHS环保要求		

P1	Wirelist
1	brown
2	blue
3	white
4	green
5	pink
6	yellow
7	black
8	grey
9	red
10	violet
11	grey/pink
12	red/blue
13	white/green
14	brown/green
15	white/yellow
16	yellow/brown
17	white/grey
Shield	Braid

F		Pipe	Shield Pipe,Copper Alloy With Nickel Plated	pcs	1
E		PUR	Molded With Black PUR	G	8
D		Housing	A-Coding Male 17PIN,Black PA66 UL94V-0	pcs	1
C		Terminal	Male Terminal ,Copper Alloy With Gold Plated	pcs	17
B		Screw	Screw M12 X1.0,Copper Alloy With Nickel Plated	pcs	1
A		Cable	UL TYPE 26AWGX17C+AL+Braid Black PVC Jacket	mm	X
编号 No.	料号 Materials.No	品名 Name	材 料 规 格 Description	单位 Unit	用量 Qty

		慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: M12-A17-ST2-M02-BCC-XXX	
NO SPECIFIED TOLERANCE		Cus' P/N:		Order No :		---		Drawing No.: SP-02-M00XXX	
LINEAR	0.5~6	±0.1	DES.	JUN	DATE	UNITS	mm	THIRD ANGLE PROJECTION	PAGE
	6~30	±0.2	CHK.		DATE	SIZE	A4		1 of 1
	>30	±2%			DATE	SIZE	A4		
ANGLES		±1°	APP.		DATE	SCALE	X:X	文件等级:外部公开	