



P1	Wirelist
1	brown
2	blue
3	white
4	green
5	pink
6	yellow
7	black
8	grey
9	red
10	violet
11	grey/pink
12	red/blue
Shield	Braid

Contacts Pin 数	12Pin
A—Coding	
Rated Current 额定电流	1.5A
Rated Voltage 额定电压	30V
Wire Range线范围	26AWG
PART NO. 品名: (1m)	M12-A12-ST2-F02-BCR-100
PART NO. 品名: (2m)	M12-A12-ST2-F02-BCR-200
PART NO. 品名: (3m)	M12-A12-ST2-F02-BCR-300
PART NO. 品名: (5m)	M12-A12-ST2-F02-BCR-500
Customized.定制	

G		Pipe	Shield Pipe,Brass With Nickel Plated	pcs	1
F		O-ring	O-ring,FKM Green	pcs	1
E		PUR	Molded With Black PUR	G	8
D		Housing	A-Coding Female 12PIN,Black PA66	pcs	1
C		Terminal	Female Terminal ,Brass With Gold Plated	pcs	12
B		Screw	Screw M12 X1.0,Brass With Nickel Plated	pcs	1
A		Cable	UL 20549 26AWG X12+AL+Braid Black PUR Jacket	mm	L
编号 No.	料号 Materials.No	品名 Name	材料规格 Description	单位 Unit	用量 Qty

 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD				PART NO.: M12-A12-ST2-F02-BCR-XXX			
NO SPECIFIED TOLERANCE		Cus' P/N:		Order No: ---		Drawing No.: SP-02-M0XXXX	
LINEAR	0.5~6	±0.1	DES.	JUN	DATE	UNITS	mm
	6~30	±0.2	CHK.		DATE	SIZE	A4
	>30	±2%					
ANGLES	±1°		APP.		DATE	SCALE	X:X
						THIRD ANGLE PROJECTION  1 of 1	
文件等级: 外部公开							