

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权,否则禁止转让、复制、利用、交还本文档的内容。侵犯者将承担赔偿责任。本公司保留对涉及发明、实用新型和外观设计的所有权利。

1


2

3

4

5

6



Contacts Pin 数	2Pin	3Pin	4Pin	5Pin
Coding 编码 A-Coding				
Rated Current 额定电流	13A	13A	13A	8A
Rated Voltage 额定电压	600V	600V	600V	600V
Wire Range 接线范围	16AWG(1.5mm ²)	16AWG(1.5mm ²)	16AWG(1.5mm ²)	16AWG(1.5mm ²)
PART NO. 品名 (1m):	M87-A02-RA0-F02-BCC-100	M87-A03-RA0-F02-BCC-100	M87-A04-RA0-F02-BCC-100	M87-A05-RA0-F02-BCC-100
PART NO. 品名 (2m):	M87-A02-RA0-F02-BCC-200	M87-A03-RA0-F02-BCC-200	M87-A04-RA0-F02-BCC-200	M87-A05-RA0-F02-BCC-200
PART NO. 品名 (3m):	M87-A02-RA0-F02-BCC-300	M87-A03-RA0-F02-BCC-300	M87-A04-RA0-F02-BCC-300	M87-A05-RA0-F02-BCC-300
PART NO. 品名 (5m):	M87-A02-RA0-F02-BCC-500	M87-A03-RA0-F02-BCC-500	M87-A04-RA0-F02-BCC-500	M87-A05-RA0-F02-BCC-500
Custiomized. 定制化:				

L=1000mm

L=2000mm

L=3000mm

L=5000mm

F		O-ring	O-ring, FKM Black	pcs	1
E		PUR	Molded With Black PUR	G	15
D		Housing	A-Coding Female, Black PA66, UL94V-0	pcs	1
C		Terminal	Female Terminal, Brass With Gold Plated	pcs	X
B		Screw	Screw 7/8, Brass With Nickel Plated	pcs	1
A		Cable	UL 2586 16AWG Black PVC Jacket	mm	L
编号 No.	料号 Materials.No	品名 Name	材料规格 Description	单位 Unit	用量 Qty

NO SPECIFIED TOLERANCE			DES.	PTQ	DATE	UNITS	mm	TYPE: CUSTOMER DRAWING		
LINEAR	0.5~6	±0.1	CHK.		DATE	SIZE	A4	Drawing No.: SP-02-M00XXX		SHEET 1 of 2
	6~30	±0.2	APP.		DATE	SCALE	1:1	Order No:XXXXXX		REV T0
	>30	±2%	 慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD					PART NO.:(see Table) M87-AXX-RA0-F02-BCC-XXX		
ANGLES	±1°									

REVISION RECORD

REV.	DESCRIPTION	ECN No.	APPROVED	DATE
T0	--	/		2022.06.08

IEC 技术参数	
IEC Technical Data	
工作温度 Operating temperatur [°C]	-25~+105
防护等级 IP Class (IN Locked condition)	IP67
额定电压 Rated Voltage [V]	_____
额定电流 Rated Current [A]	_____
导线截面积 Conductor cross section 硬质/柔性导线 Solid/ flexible [mm²]	
接线范围 Wire Range 单/多芯线 Solid/Stranded [AWG]	
材 料 Material	
绝缘材料 Insulation Material	PA 66
阻燃等级 Imflammability	UL94V-0
导体材料 Contactor Material	铜合金 Copper alloy
导体镀层 Contactive Coating	镀金 Gold Plated
螺母/螺丝 Connector Nut/Screw	镀金 With Nickel Plated铜镀镍
符合RoHS环保要求	

1

2

3

4

5

FOR-0371 Rev.1.0

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权,否则禁止转让、复制、利用、交还本文件的内容。侵犯者将负赔偿责任。本公司保留对涉及发明、实用新型和外观设计的所有权利。

1

2

3

4

5

6

REVISION RECORD

REV.	DESCRIPTION	ECN No.	APPROVED	DATE
T0	--	/		2022.06.08

P1 Wirelist
1 brown
2 blue

P1 Wirelist
1 green/yellow
2 brown
3 blue

P1 Wirelist
1 black
2 blue
3 brown
4 white

P1 Wirelist
1 black
2 blue
3 green/yellow
4 brown
5 white

IEC 技术参数	
IEC Technical Data	
工作温度 Operating temperatur [°C]	-40~+105
防护等级 IP Class (IN Locked condition)	IP67
额定电压 Rated Voltage [V]	_____
额定电流 Rated Current [A]	_____
导线截面积Conductor cross section	
硬质/柔性导线 Solid/ flexible [mm²]	
接线范围 Wire Range	
单/多芯线 Solid/Stranded [AWG]	
材料 Material	
绝缘材料 Insulation Material	PA 66
阻燃等级 Imflammability	UL94V-0
导体材料 Contactor Material	铜合金 Copper alloy
导体镀层 Contactive Coating	镀金 Gold Plated
螺母/螺丝 Connector Nut/Screw	Brass With Nickel Plated铜镀镍
符合RoHS环保要求	

NO SPECIFIED TOLERANCE			DES.	PTQ	DATE		UNITS	mm	TYPE: CUSTOMER DRAWING	
LINEAR	0.5~6	±0.1	CHK.		DATE		SIZE	A4	Drawing No.: SP-02-M00XXX	SHEET 2 of 2
	6~30	±0.2	APP.		DATE		SCALE	1:1	Order No:XXXXXX	REV T0
	>30	±2%								
ANGLES	±1°		慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD				PART NO.:(see Table) M87-AXX-RA0-F02-BCC-XXX			

1

2

3

4

5

FOR-0371 Rev.1.0