




Contacts Pin 数	12Pin
A—Coding	
Rated Current 额定电流	1.5A
Rated Voltage 额定电压	30V
Wire Range线范围	26AWG
PART NO. 品名: (1M)	M12-A12-ST0-M02-SCR-100N
PART NO. 品名: (2M)	M12-A12-ST0-M02-SCR-200N
PART NO. 品名: (3M)	M12-A12-ST0-M02-SCR-300N
PART NO. 品名: (5M)	M12-A12-ST0-M02-SCR-500N
Custiomized. 定制化	

P1	Wirelist
1	brown
2	blue
3	white
4	green
5	pink
6	yellow
7	black
8	grey
9	red
10	violet
11	grey/pink
12	red/blue

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE

IEC 技术参数		IEC61076-2-101
IEC Technical Data		
工作温度 Operating temperatur [°C]	-25~+80	
防护等级 IP Class (IN Locked condition)	IP67	
额定电压 Rated Voltage [V]	30	
额定电流 Rated Current [A]	1.5	
导线截面积Conductor cross section 硬质/柔性导线 Solid/ flexible [mm²]	0.14	
接线范围 Wire Range 单/多芯线 Solid/Stranded [AWG]	26	
材 料 Material		
绝缘材料 Insulation Material	PA 66	
阻燃等级 Imflammability	UL94V-0	
导体材料 Contactor Material	铜合金 Copper alloy	
导体镀层 Contactive Coating	镀金 Gold Plated	
螺母/螺丝 Connector Nut/Screw	不锈钢 Stainless steel	
符合RoHS环保要求		

E	TPU	Molded With Black TPU	G	8
D	Housing	A—Coding Male 12PIN,Black PA66	pcs	1
C	Terminal	Male Terminal ,Brass With Gold Plated	pcs	12
B	Screw	Screw M12 X1.0,Stainless steel	pcs	1
A	Cable	UL TYPE 26AWG X12C Black PUR Jacket	mm	L
编号 No.	料号 Materials.No	品名 Name	材料规格 Description	单位 Unit
				用量 Qty

						慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD				PART NO.: M12-A12-ST0-M02-SCR- <u>XXXX</u>					
NO SPECIFIED TOLERANCE						Cus' P/N:		Order No :		---		Drawing No.:		SP-02-M00XXX	
LINEAR	0.5~6	±0.1	DES.	JUN	DATE	UNITS	mm	THIRD ANGLE PROJECTION				PAGE			
	6~30	±0.2													
	≥30	±2%													
ANGLES	±1°		APP.		DATE	SCALE	X:X	文件等级:外部公开							