

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除特别声明外，未经许可，不得复制或传播本文件内容。本公司保留对涉及发明、实用新型和外观设计的所有权利。

1

2

3





4

5

6

REVISION RECORD

REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		YuCZ	24.08.15



General Tolerances

variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30

UL/CUL 技术 参数		UL1059		
UL/CUL	Technical Data			
等 级	Use Group	B	C	D
额定电压	Rated Voltage [V]	150	/	—
额定电流	Rated Current [A]	6	/	—
接线范围	Wire Range	/		
单/多芯线	Solid/Stranded [AWG]			
耐电压	Withstanding Voltage	1300V/1Min		
IEC 技术参数		IEC 61984		
IEC Technical Data				
过电压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	32	160	160
额定电流	Rated Current [A]	6	6	6
额定冲击电压	Impulse withstand voltage [KV]	2.5	2.5	2.5
导线截面积	Conductor cross section	/		
硬质/柔性导线	Solid/ flexible [mm ²]			
一般参数 Other Data				
间距 Pitch / 极数 Poles	[mm] / [P]	2.54 /02~24		
工作温度	Operating temperature [°C]	-40~130		
焊接方式	Soldering method	Reflow Soldering		
符合RoHS环保要求				
2	Pin	Copper Alloy	Sn Plated	
1	Housing	HIGH-TEMPERATURE PLASTICS	UL94V-0	
ITEM	NAME OF PART	MATERIAL	NOTES	

DES.	YuCZ	DATE	24.08.15	UNITS	mm	THIRD ANGLE PROJECTION	
CHK.	YangHJ	DATE	24.08.15	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1
APP.	JASON	DATE	24.08.15	SCALE	4:1	DRAWING TYPE: SP-03	REV V0
慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ15RD-THR-2.54-XXP-1Y-00A	

1

2

3

4

5

FOR-0371 Rev.1.0