




Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除特别声明外，未经许可，不得复制或传播本文件内容。本公司保留对涉及发明、实用新型和外观设计的所有权利。



General Tolerances										— □ ⊥	
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100		
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60	

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		YuCZ	23.12.11

UL/CUL 技术参数		UL/CUL Technical Data			cULus		
等级	Use Group	B	C	D			
额定电压	Rated Voltage [V]	300	-	300			
额定电流	Rated Current [A]	8	-	8			
接线范围	Wire Range						
单/多芯线	Solid/Stranded [AWG]						
耐电压	Withstanding Voltage	1600V/1Min					
IEC 技术参数		IEC61984					
IEC Technical Data							
过电压类别	Overvoltage Category	III	III	II			
污染等级	Contamination Class	3	2	2			
额定电压	Rated Voltage [V]	160	160	250			
额定电流	Rated Current [A]	8	8	8			
额定冲击电压	Impulse withstand voltage [KV]	2.5	2.5	2.5			
导线截面积	Conductor cross section						
硬质/柔性导线	Solid/flexible [mm²]						
一般参数		Other Data					
间距	Pitch / 极数 Poles [mm] / [P]	3.81 / 02-24					
工作温度	Operating temperature [°C]	-40~130					
焊接方式	Soldering method	Reflow Soldering					
符合RoHS环保要求							
3	NUT	Copper Alloy	M2.5				
2	Pin	Copper Alloy	Sn Plated				
1	Housing	LCP	UL94V-0				
ITEM	NAME OF PART		MATERIAL		NOTES		

DES.	YuCZ	DATE	23.12.11	UNITS	mm	THIRD ANGLE PROJECTION		
CHK.	YangHJ	DATE	23.12.11	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1	
APP.	JASON	DATE	23.12.11	SCALE	3:1	DRAWING TYPE: SP-03	REV	V0
慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ15EDGVM-THR-3.81-XXP-1Y-00A		

FOR-0371 Rev.1.0