

[illegible]

REVISION RECORD										
REV.	ESCRIPTION			ECN No.	APPROVED	DATE				
0	新发行				YuCZ	24.08.20				
				UL/CUL 技术参数 UL/CUL Technical Data			UL1059			
				等 级 Use Group		B	C	D		
				额定电压 Rated Voltage [V]		300	-	300		
				额定电流 Rated Current [A]		16	-	10		
				接线范围 Wire Range		-				
				单/多芯线 Solid/Stranded [AWG]						
				耐电压 Withstanding Voltage		1600V/1Min				
				IEC 技术参数 IEC Technical Data				IEC61984		
				过电压类别 Overvoltage Category		III	III	II		
				污染等级 Contamination Class		3	2	2		
				额定电压 Rated Voltage [V]		250	320	400		
				额定电流 Rated Current [A]		12	12	12		
				额定冲击电压 Impulse withstand voltage [KV]		4.0	4.0	4.0		
				导线截面积 Conductor cross section		-				
				硬质/柔性导线 Solid/ flexible [mm²]						
				一般参数 Other Data						
				间距 Pitch /极数 Poles [mm]/[P]		5.0 / 02P-24P				
				剥线长度 Stripping Length [mm]		-				
				螺丝 Screw/扭矩 Torque(Max) [N.m]		-				
				工作温度 Operating temperature [°C]		-40~130				
焊接方法 Soldering method		Reflow Soldering								

YuCZ	DATE	24.08.20	UNITS	mm	THIRD ANGLE PROJECTION	
YangHJ	DATE	24.08.20	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1
JASON	DATE	24.08.20	SCALE	4:1	DRAWING TYPE: SP-03	REV 0



慈溪市万捷电子有限公司
CIXI WANJIE ELECTRONIC CO., LTD

PART NO.:
WJ332J-THR-5.0-XXP-1Y-00A