





Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除奉命于明确授权，否则禁止转让、复制、利用、交还本文件的内容。侵犯者须负赔偿法律责任。本公司保留全部知识产权。



REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		WangP	23.11.30

UL/CUL 技术参数				
UL/CUL Technical Data				
等级	Use Group	B	C	D
额定电压	Rated Voltage [V]	300	-	300
额定电流	Rated Current [A]	30	-	10
接线范围	Wire Range	26-10		
单/多芯线	Solid/Stranded [AWG]			
耐电压	Withstanding Voltage	1600V/1Min		
IEC 技术参数				
IEC Technical Data				
过电压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	500	630	1000
额定电流	Rated Current [A]	32	32	32
额定冲击电压	Impulse withstand voltage [KV]	6.0	6.0	6.0
导线截面积	Conductor cross section	0.2-4.0		
硬质/柔性导线	Solid/flexible [mm ²]			
一般参数		Other Data		
间距	Pitch / 极数 Poles [mm] / [P]	7.62 / 02~24		
剥线长度	Stripping Length [mm]	6~7		
螺丝	Screw/扭矩 Torque(Max) [N.m]	M3/0.5		
工作温度	Operating temperature [°C]	-40~105		
焊接方法	Soldering method	Wave soldering		

General Tolerances								— □ ⊥		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100	
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

4	Screw	Steel	M3/Zn Plated	DES.	WangP	DATE	23.11.30	UNITS	mm	THIRD ANGLE PROJECTION	
3	Cage	Copper Alloy	M3/ Ni Plated	CHK.	YangHJ	DATE	23.11.30	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1
2	Header Pin	Copper Alloy	Sn Plated	APP.	JASON	DATE	23.11.30	SCALE	2.5:1	DRAWING TYPE: SP-03	REV V0
1	Housing	PA66	UL94V-0								
ITEM	NAME OF PART	MATERIAL	NOTES								

慈溪市万捷电子有限公司
 CIXI WANJIE ELECTRONIC CO., LTD

PART NO.:
 WJ762-7.62-XXP-1Y-00A