



REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		YuCZ	23.12.11



UL/CUL 技术参数		UL/CUL Technical Data			
等级	Use Group	B	C	D	
额定电压	Rated Voltage [V]	300	-	300	
额定电流	Rated Current [A]	15	-	10	
接线范围	Wire Range	28-12			
单/多芯线	Solid/Stranded [AWG]				
耐电压	Withstanding Voltage	1600V/1Min			
IEC 技术参数		IEC61984			
过电压类别	Overvoltage Category	III	III	II	
污染等级	Contamination Class	3	2	2	
额定电压	Rated Voltage [V]	250	320	630	
额定电流	Rated Current [A]	12	12	12	
额定冲击电压	Impulse withstand voltage [KV]	4.0	4.0	4.0	
导线截面积	Conductor cross section	0.2-2.5			
硬质/柔性导线	Solid/flexible [mm ²]				
一般参数		Other Data			
间距	Pitch / 极数 Poles [mm] / [P]	5.0 / 06-24			
剥线长度	Stripping Length [mm]	7-8			
螺丝	Screw/ 扭矩 Torque(Max) [N.m]	M3/0.5			
工作温度	Operating temperature [°C]	-40~105			
符合RoHS环保要求					
6	Din	PA66	UL94V-0		
5	Screw	Steel	M3/Zn Plated		
4	Cage	Copper Alloy	M3/Ni Plated		
3	Pin	Copper Alloy	Sn Plated		
2	Cover	PA66	UL94V-0		
1	Housing	PA66	UL94V-0		
ITEM	NAME OF PART	MATERIAL	NOTES		

DES.	YuCZ	DATE	23.12.11	UNITS	mm	THIRD ANGLE PROJECTION	
CHK.	YangHJ	DATE	23.12.11	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1
APP.	JASON	DATE	23.12.11	SCALE	3:2	DRAWING TYPE: SP-03	REV V0
慈溪市万捷电子有限公司 CIXI WANJIE ELECTRONIC CO., LTD						PART NO.: WJ2EDGRK-5.0-XXP-1Y-00A	

General Tolerances										
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	to 10	over 10 to 100	to 100	
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权，否则禁止转让、复制、利用、交流本文件的内容。侵犯者需负赔偿责任。未经许可不得复制或传播本文件内容。

1 2 3 4 5 6

1 2 3 4 5 6 FOR-0371 Rev.1.0