




REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE
V0	新发行		YuCZ	23.12.11



UL/CUL	技术参数	UL/CUL		
UL/CUL	Technical Data	Technical Data		
等级	Use Group	B	C	D
额定电压	Rated Voltage [V]	300	-	300
额定电流	Rated Current [A]	15	-	10
接线范围	Wire Range	28-12		
单/多芯线	Solid/Stranded [AWG]	28-12		
耐电压	Withstanding Voltage	1600V/1Min		

IEC	技术参数	IEC		
IEC	Technical Data	Technical Data		
过电压类别	Overvoltage Category	III	III	II
污染等级	Contamination Class	3	2	2
额定电压	Rated Voltage [V]	250	320	630
额定电流	Rated Current [A]	12	12	12
额定冲击电压	Impulse withstand voltage [KV]	4.0	4.0	4.0
导线截面积	Conductor cross section	0.2-2.5		
硬质/柔性导线	Solid/flexible [mm ²]	0.2-2.5		

一般参数		Other Data	
间距	Pitch / 极数 Poles [mm] / [P]	5.08 / 06-24	
剥线长度	Stripping Length [mm]	7-8	
螺丝	Screw/ 扭矩 Torque(Max) [N.m]	M3/0.5	
工作温度	Operating temperature [°C]	-40~105	

符合RoHS环保要求			
ITEM	NAME OF PART	MATERIAL	NOTES
7	NUT	Copper Alloy	M2.5
6	Din	PA66	UL94V-0
5	Screw	Steel	M3/Zn Plated
4	Cage	Copper Alloy	M3/Ni Plated
3	Pin	Copper Alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

DES.	YuCZ	DATE	23.12.11	UNITS	mm	THIRD ANGLE PROJECTION	
CHK.	YangHJ	DATE	23.12.11	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1
APP.	JASON	DATE	23.12.11	SCALE	3:2	DRAWING TYPE: SP-03	REV V0

慈溪市万捷电子有限公司
 CIXI WANJIE ELECTRONIC CO., LTD
 PART NO.: WJ2EDGURKM-5.08-XXP-1Y-00A

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非经予书面授权，否则禁止转让、复制、利用、交流本文件的内容。侵犯者将承担赔偿责任。本公司保留对涉及发明、实用新型专利的所有权利。

General Tolerances								— □ ⊥		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	to 10	over 10 to 100	to 100	
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60